


## survivor 100 eco **suspended**



- IK15** - 125 joules impact resistance  
**IP66** - hermetically sealed light module cassette  
**AT06** - security torx tamper-proof fasteners

### description

Extruded aluminium mounting base with durable polyester powder coat finish and impact-resistant GRP security caps  
Impact-resistant UV-stabilised high-transmission polycarbonate light module diffuser  
Serviceable replaceable and upgradable light module cassette  
Internal socket drive security-torx 304 stainless steel security fasteners  
Integral energy efficient Zhaga compliant Tridonic LED modules and power supply unit  
Heavy-gauge stainless steel wire suspensions  
Internal stainless steel wire safety lanyards  
1.0 m circular flex connection

### applications

highly robust suspended luminaire that enhances safety and security in challenging environments. a durable construction ensures dependable operation and superior performance under harsh operating conditions; ideal for applications such as transportation, custodial, public areas, and secure healthcare

### country of origin

Australia

### accreditations

Australian Made and Owned  
DALI alliance  
EESS  
RCM

### warranty

7-year standard  
10-year on application

### standards

AS/NZS 60598.1:2017  
AS/NZS 60598.2.1:2014  
AS/NZS 60598.2.22:2019  
AS/NZS 2293.3:2018  
IEC/EN 62262:2002+A1:2021  
AS 60529-2004  
ANSI/IES LM-79-19  
ANSI/IES LM-80-21  
ANSI/IES TM-21-21

## survivor 100 eco **suspended**



### options

#### finishes

black texture • white texture polyester powder coat  
additional non-standard powder coat colours  
35-year warranty powder coat on request

#### control system

DALI-2 • fixed output • Casambi wireless • switchDIM • 0-10 V

#### colour rendering index [CRI]

80+ • 90+

#### correlated colour temperature [CCT]

2700 K • 3000 K • 3500 K • 4000 K • 5000 K • 6500 K • tunable white

#### coloured LEDs

RGB • RGB+W • RGBW • RGBW+W • red • green • blue

#### electrical connection


IP68 quick-connect plug+socket • IP20 plug

#### sensors

type microwave • passive infrared  
control system DALI-2 • Casambi wireless • basic on/off  
detection mode presence • ambient light

#### emergency packs

type integrated  
monitoring system DALI-2 • OEM proprietary  
operating mode maintained • non-maintained • sustained



#### weights + dimensions [kg / mm]

nominal	L	W	H	weight
500	460	112	99	1.9
700	690	112	99	2.7
1000	970	112	99	3.7
1200	1250	112	99	4.7
1500	1530	112	99	5.7
1800	1810	112	99	6.8
2100	2090	112	99	8.4
2400	2370	112	99	9.6
2600	2650	112	99	10.4
2900	2930	112	99	11.6

### integrated lighting systems

#### description

fully integrated and modular plug-n-play lighting systems for the most challenging and robust environments. every system is custom-manufactured in Australia using high-quality materials. supplied in pre-fabricated sections with pre-wired light module cassettes, and interconnecting IP68 quick-connect leads; making installation and maintenance effortless. available with multiple circuits, control systems, light sources, finishes, sensors, and emergency packs

#### sensors

type microwave • passive infrared  
control system DALI-2 • Casambi wireless • basic on/off  
detection mode presence • ambient light

#### emergency packs

type integrated  
monitoring system DALI-2 • OEM proprietary  
operating mode maintained • non-maintained • sustained

survivor 100 eco **suspended**



CRI 80+ | CCT 3000 K | **830**

nominal length	20%		40%		60%		80%		100%	
	lumens	watts	lumens	watts	lumens	watts	lumens	watts	lumens	watts
500	290	2.5	580	5	880	7.5	1170	10	1460	12.5
700	580	5	1170	10	1750	15	2330	20	2920	25
1000	880	7.5	1750	15	2620	22.5	3500	30	4370	37.5
1200	1170	10	2330	20	3500	30	4670	40	5830	50
1500	1460	12.5	2920	25	4370	37.4	5830	49.9	7290	62.4
1800	1750	15	3500	30	5250	44.9	7000	59.9	8750	74.9
2000	2040	17.5	4080	35	6120	52.5	8170	70	10210	87.5
2400	2330	20	4670	40	7000	60	9330	80	11660	100
2600	2630	22.5	5250	45	7870	67.5	10500	90	13120	112.5
2900	2920	25	5830	50	8750	75	11660	100	14580	125

CRI 80+ | CCT 4000 K | **840**

nominal length	20%		40%		60%		80%		100%	
	lumens	watts	lumens	watts	lumens	watts	lumens	watts	lumens	watts
500	300	2.5	610	5	910	7.5	1220	10	1520	12.5
700	610	5	1220	10	1830	15	2440	20	3050	25
1000	920	7.5	1830	15	2740	22.5	3660	30	4570	37.5
1200	1220	10	2440	20	3660	30	4880	40	6100	50
1500	1530	12.5	3050	25	4580	37.4	6100	49.9	7630	62.4
1800	1830	15	3660	30	5490	44.9	7330	59.9	9160	74.9
2000	2140	17.5	4270	35	6410	52.5	8540	70	10680	87.5
2400	2440	20	4880	40	7320	60	9760	80	12200	100
2600	2740	22.5	5490	45	8230	67.5	10980	90	13720	112.5
2900	3050	25	6100	50	9150	75	12200	100	15240	125

photometric data is nominal and intended for general information purposes only. it is not to be relied upon nor used in place of photometry files issued by Survivor Lighting Pty Ltd  
± 5% measurement uncertainty

